

**INFORMATION CONTROL SYSTEM, INFORMATION PROCESSING SUPPORT
SERVER, INFORMATION PROCESSING TERMINAL, INFORMATION
PROCESSING METHOD, STORAGE STORING INFORMATION PROCESSING
PROGRAM, AND PROGRAM TRANSMISSION APPARATUS**

DESCRIPTION

1. Field of the Invention

The present invention relates to an information processing method for supporting collaboration for which WWW (Web) contents are used and which is performed by a plurality of clients.

2. Related Art

Today, in the WWW widely used in the Internet, collaboration technology is proposed, the collaboration technology with which a plurality of users perform collaboration (access, movement, modification, etc.) on Web-page. Figure 14 is a diagram showing an example of applying this collaboration on Web-page to customer counseling service. In this service, a customer terminal 1410 which a customer uses and an agent terminal 1420 that an agent corresponding to customer's consultation uses are connected via a communication network. In a state shown in Figure 14, the customer terminal 1410 and agent terminal 1420 display Web-pages 1411 and 1421 that are the same. Here, since the customer terminal 1410 and agent terminal 1420 are synchronized by software providing the collaboration, an operation which the customer performs on the Web-page 1411 by using the customer terminal 1410 is reflected in the Web-page 1421 displayed in the agent terminal 1420. Similarly, an operation which the agent performs on the Web-page 1421 by using the agent terminal 1420 is reflected in the Web-page 1411 displayed in the customer terminal 1410. Therefore, by the customer and agent performing operations such as mutual writing on the same Web-page, it becomes possible to provide such service that the agent corresponds to customer's consultation.

By the way, in public networks such as the Internet, it is forbidden from the viewpoint of their publicness for a user to arbitrarily add or modify information on the networks. On the other hand, Published Unexamined Patent Application No. 10-21263, the technology of adding user's unique information is proposed, the technology, which is realized by associating additional data with main data without modifying the main data registered in a network. Owing to this, the user can perform an operation such as addition of annotation data to Web-page that the user accesses.

SUMMARY OF THE INVENTION

In consideration of such problems, a method is conceivable, the method which is such a method that a user informs an agent of the contents of a question via an e-mail or the like beforehand, and

If the conventional technology associating attached-information with the Web-page described above can be used so as to accurately express the contents of the question, it is convenient since it is possible to add information such as indicating a questionable place directly with an arrow.

In addition, another object is to make it possible to automatically deliver the WWW contents with attached-information to predetermined users.

For these objects, the present invention provides an information control system supporting the collaboration for which a Web content are used and which is performed with a plurality of information processing terminals, the information control system comprising an information processing support server connected to Web server via a communication network, and the plurality of information processing terminals that obtain the Web content, provided by the Web server via the information processing support server, and perform work using this WWW contents, the information

The transmission and reception of data between this information processing support server and information processing terminal can be performed, for example, via a TCP/IP network. Therefore, it is possible to perform, for example, communication itself between the information processing support server and information processing terminal via various types of networks such as dial-up connection by using a public telephone network, and a LAN installed in a company.

- 4 -

Furthermore, this information control system is characterized in that this information control system includes at least data filled in a form for the Web content as attached-information, in the information processing support server, the attached-information managing-section associates a URL of the Web content with the data itself filled in the form, and the attached-information transmitter embeds the data, which is filled and is associated with the URL of this a Web content, in a form of the Web content relating to an access request according to the access request from an information processing terminal and transmits the Web content to the information processing terminal, and the information processing terminal displays the Web content, in the form of which the filled data is embedded, by using a browser. According to this configuration, it becomes possible to realize the sharing of filled data even if the data is filled in the form of a Web content, and to reproduce the Web content in such a state that the data is filled.

This information control system is characterized in that the URL list generator in this information processing support server generates a URL list as a Web content, and the information processing terminal requests the information processing support server to obtain a Web content, where attached-information is

In addition, if this information control system is characterized in that the URL list generator in the information processing support server recognizes a user of the information processing terminal, and generates a URL list of the Web content that this user can access, this is preferable at a point of being capable of easily providing means for performing collaboration only between specific users.

Furthermore, if this information control system is characterized in that the URL list generator in the information processing support server sets a Web content, which a user can access, on the basis of a kind of the Web content of attached-information, it is possible to arbitrarily set users performing collaboration.

The present invention provides an information control system supporting collaboration for which a Web content are used and which is performed with a plurality of information processing terminals, the information control system comprising the plurality of information processing terminals each of which is connected to Web server via a communication network, obtains a Web content provided by the Web server, and adds predetermined attached-information as work for the Web content, and an information processing support server that associates the attached-information, added to the Web content by the information processing terminal, with a URL of this a Web content and retains them, this information processing support server returning the attached-information corresponding to an access request to the information processing terminal at the time of receiving the access request, corresponding to a URL associated with the attached-information, from the information processing terminal, this information processing terminal receiving this

The present invention provides a following information processing support server supporting collaboration for which a Web content are used and which is performed with a plurality of information processing terminals. Thus, this information processing support server comprises a cache manager obtaining a Web content from Web server, connected to a communication network, according to an access request from an information processing terminal, transmitting the Web content, which are obtained, to the information processing terminal having issued the access request, and a session information controller recognizing the start of a session by the information processing terminal owing to the access request received from the information processing terminal, managing session information including a URL of a Web content that will be processed in this session, receiving attached-information added to the Web content by the information processing terminal, and managing this session information and this attached-information with associating them with each other.

- 7 -

In addition, the session information controller is characterized in that the session information controller embeds filled data in a form of a Web content and allows a transmission and receiving section to transmit the Web content to the information processing terminal if the Web content obtained in the session recognized are a Web content with a form, and data filled in the form is associated with its URL as attached-information. According to this configuration, the session information controller is preferable at a point of being capable of performing collaboration in the shape of filling a comment into a Web content with a form, responding to the comment, or the like.

The present invention provides the following information processing terminal. Thus, the information processing terminal comprises a connecting section for sending and receiving data including a Web content with being connected to Web server, and a browser displaying a Web content received from the server via this connecting section, adding predetermined attached-information to a Web content displayed, and transmitting a Web content to the

server via the connecting section, this browser being capable of synthesizing and displaying a Web content and annotation data if the data received from the server is a Web content and annotation data as attached-information added to a Web content. In this manner, this becomes an excellent information processing terminal at a point of being capable of supporting the work of adding annotation data to a Web content or modifying the annotation data, as collaboration.

In addition, this browser is characterized in that this browser obtains annotation data by using a file name, synthesizes a Web content and annotation data, and displays them if the data received from the server is a Web content and the file name of annotation data as attached-information added to a Web content, and this annotation data can be obtained from predetermined storage apparatus except the Web server. According to this configuration, since it is not necessary to reproduce annotation data in the server, a response to an access becomes fast, and hence this is preferable at a point of being capable of performing collaboration in an environment further comfortable.

In addition, the present invention comprises a connecting section for transmitting and receiving data including a Web content with being connected to a server via a communication network, a synthesis processor obtaining a Web content with a URL via the communication network and synthesizing a Web content and attached-information at the time of receiving this attached-information, associated with a predetermined URL, from the server via this connecting section, and a browser displaying a Web content, which are received from the server via the connecting section and with which the attached-information is synthesized by the synthesis processor, adding predetermined attached-information to a Web content displayed, and transmitting a Web content to the server via the connecting section.

The present invention provides the following information processing method for supporting collaboration for which a Web

content are used and which is performed with a plurality of information processing terminals. Thus, the information processing method includes a step of adding predetermined attached-information to a Web content, a step of associating the attached-information, added to a Web content, with a URL of a Web content and retaining them, and a step of transmitting a Web content, having the URL, and the attached-information, associated with the URL, to the source of the access request according to the access request corresponding to the URL associated with the attached-information.

Here, this information processing method is characterized in that at least annotation data for performing drawing on a Web content is included as attached-information at the step of adding attached-information, the step of retaining the attached-information includes a step of generating a data file after receiving annotation data and associating a file name of this data file with a URL of a Web content if the attached-information is the annotation data, and the step of adding attached-information to a Web content includes a step of adding the data file of annotation data specified by a file name to a Web content if information associated with the URL is this file name of the annotation data and further includes a step of synthesizing a Web content and the annotation data at the time of displaying a Web content. According to this configuration, even if annotation data is added as attached-information to a Web content, it is possible to reproduce the annotation data, which is added, at the time of displaying a Web content.

In addition, this information processing method is characterized in that at least data filled in a form of a Web content is included as attached-information at the step of adding attached-information, the step of retaining attached-information includes a step of associating data itself to a Web content if the attached-information is this data filled in the form, and the step of adding attached-information to a Web content includes a step of embedding the data, filled in a form, in a concerned place of a

Web content having this form if information associated with a URL is the data filled in the form. According to such configuration, it is possible to display a Web content in such a state that data is filled if the data is filled in the form of a Web content.

In addition, before the step of adding attached-information, this information processing method is characterized by further comprising a step of generating a URL list of a Web content having attached-information that are associated at the step of retaining the attached-information. According to this configuration, this information processing method is preferable at a point of being capable of easily retrieving a Web content, where attached-information is added, by referring to this URL list.

Furthermore, the step of generating a URL list is characterized by including a step of recognizing users of information processing terminals, and a step of generating a URL list of a Web content that the users can access. According to this configuration, it is possible to perform collaboration only between specific users.

According to the present invention, a storage is provided, the storage, which stores an information processing program, executed by a computer, so that input means of the computer can read the information processing program. The information processing program stored in this storage is an information processing program making a computer execute the processing of obtaining a Web content from Web server, connected to a communication network, according to an access request from an information processing terminal and transmitting a Web content to the information processing terminal having issued the access request, the processing of receiving attached-information added to a Web content by the information processing terminal and retaining the attached-information and a Web content with associating them with each other, and the processing of adding this attached-information to a Web content and transmitting a Web content to the information processing terminal if the attached-information has already been associated with a URL of a Web content obtained according to the

According to the present invention, a storage is provided, the storage, which stores an information processing program, executed by an information processing terminal, so that the input means of the information processing terminal can read the information processing program. The information processing program stored in this storage is an information processing program making the information processing terminal execute the processing of receiving a Web content from a server and displaying a Web content, the processing of synthesizing a Web content and annotation data before the display processing if the annotation data is added to a Web content received from the server, the processing of adding predetermined attached-information to a Web content displayed, and the processing of transmitting this attached-information, which is added, to the server. Owing to this, it becomes possible to use all the information processing terminals, in each of which such an information processing program can be installed, as terminals for performing collaboration.

According to the present invention, a storage is provided, the storage, which stores an information processing program, executed by an information processing terminal, so that the input means of the information processing terminal can read the information processing program. The information processing program stored in this storage is characterized by making the information processing terminal execute the processing of receiving attached-information associated with a predetermined URL by a server, the processing of obtaining a Web content having the URL corresponding to the attached-information received, the processing of synthesizing a Web content and attached-information that are obtained, and the processing of displaying a Web content where the attached-information is synthesized.

- 12 -

processing of receiving a Web content from a server and displaying a Web content, the processing of synthesizing a Web content and annotation data before the display processing if the annotation data is added to a Web content received from the server, the processing of adding predetermined attached-information to a Web content displayed, and the processing of transmitting this attached-information, which is added, to the server, and transmission means for reading the program from this storage means and transmitting this program. Therefore, it becomes possible to use all the information processing terminals, into each of which such an information processing program can be down-loaded from this program transmission apparatus and can be installed, as terminals for performing collaboration.

An information control system according to the present invention comprises a plurality of information processing terminals and an information processing support server supporting collaboration for which a Web content are used and which is performed with this plurality of information processing terminals, and is characterized in that the information processing support server comprises storage means for storing a program executed by the plurality of information processing terminals, and transmission means for reading this program from the storage means according to a request from the information processing terminal and transmitting this program, the program which is stored in this storage means and makes the information processing terminal execute the processing of receiving a Web content and displaying a Web content, the processing of adding predetermined attached-information to a Web content displayed, the processing of transmitting this attached-information, which is added, to the information processing support server, and the processing of synthesizing a Web content and annotation data at the time of receiving a Web content and annotation data associated with this a Web content. According to such configuration, it becomes possible to use all the information processing terminals, each of which can access the information processing support server and down-load such an information processing program, which is installed in each

Figure 14 is a diagram for explaining conventional collaboration technology.

Hereinafter, this invention will be described in detail on the basis of embodiments shown in the drawings.

- 15 -

The information processing support server 100 comprises Web server 120, a server application 121 operating in the Web server 120, a cache manager 122, a URL list generator 123 and a URL list selector 124, a session manager 130, a UAI manager 140, and an access right checker 150. In addition, the information processing support server 100 comprises, as tables used for information processing, an access right control table 161 for controlling users' access rights, a URL attached-data control table 162 for controlling attached-information added to WWW contents, and a condition list 163 for setting conditions of WWW contents that users can refer to. Furthermore, the information processing support server 100 can be realized by an ordinary computer system having a communication function such as a personal computer or a workstation. Therefore, although this is not described in the drawing, as hardware configuration, the information processing support server 100 comprises a CPU, memory, an external storage apparatus such as a hard disk drive storing programs, operating in the CPU, and data such as various types of tables described above, and a connection interface for connecting the information

The server application 121 operating in the Web server 120 supports collaboration on WWW contents by the plurality of information processing terminals 200 with a client application 220 installed in the information processing terminal 200 described later. In addition, the server application 121 recognizes the start of a session by an access request from the information processing terminal 200, verifies a user's access right by using the access right checker 150, and obtains a UAI (User Access Identification) by using the UAI manager 140.

In this embodiment, the attached-information is managed by using the URL attached-data control table 162. The URL attached-data control table 162 is generated by the cache manager 122 when the server application 121 recognizes the start of a session by an

access request from the information processing terminal 200. Then, as shown in Figure 8, a session ID, a user's log-on ID, date and time when the session was performed, and information such as a URL, attached-information, and a transaction name of the WWW contents, which is an object of work, are registered in each line of the URL attached-data control table 162. Here, the "session ID" means "ID information for specifying a session supported by the information processing support server 100." The "log-on ID" does "ID information for specifying a user." As the attached-information, if form data is added, the form data itself is registered. In addition, if annotation data is added, only a file name of the annotation data is registered, and the annotation data is made to be retained in the session manager 130. In this manner, although, in this embodiment, only the form data and annotation data is exemplified, it is possible to add various data as the attached-information by taking a style of being capable of managing objects besides the form data and annotation data by the cache manager 122. Moreover, also when attached-information is added on the way to an original destination to the same URL (WWW contents) and subsequent work is freshly performed, it becomes possible to easily recognize at what stage the attached-information is by registering a name of the work at this time as a transaction name.

The URL list generator 123 generates a URL list of WWW contents where attached-information is added by a CGI program according to a request from the information processing terminal 200. The URL list is generated as WWW contents as shown in Figure 13 by using, for example, a format of HTML. Owing to this, by displaying the URL list in the information processing terminal 200 as described later, it is possible to access the WWW contents of the URL by clicking the desired URL.

Here, the URL list generator 123 recognizes a user of the information processing terminal 200 who issued a URL list generation request, and generates the URL list with making only the WWW contents, which the user can access, as an object. In

As shown in Figure 9, information such as a user's log-on ID, a URL of WWW contents (an assigned URL), a customer ID, date and time when the session was opened, or the like are registered in each line of the condition list 163. Then, it is possible to set conditions of listing only the URLs, in which each user is registered, for the user having a predetermined log-on ID, listing a URL concerned only when attached-information is added by each user having a customer ID registered, listing only URLs where a session is opened at the date and time that are registered, or the like. Moreover, URLs to be listed can be determined by arbitrarily combining these conditions. Thus, it is possible to set a condition of listing only the URLs which satisfy all the conditions, or listing a URL if the URL meets any one of conditions, or the like.

- 19 -

As shown in Figure 1, the session manager 130 comprises a session managing section 131 and an annotation reproducer 132. The session managing section 131 assigns a session ID every session. Then, the session managing section 131 makes the cache manager 122 retain the session ID, which is assigned, with combining the session ID with a UAI given from the UAI manager 140 described later. In addition, when annotation data is added to WWW contents by the information processing terminal 200, the session managing section 131 generates an annotation data file 170 to retain the annotation data. When instructed by the URL list selector 124 to add annotation data to WWW contents, the annotation reproducer 132 reads the annotation data from the annotation data file 170 generated by the session managing section 131, and simulates the occurrence of the annotation to send its result to the information processing terminal 200.

The UAI manager 140 gives a new UAI according to a request from the server application 121 when a session is started. The access right checker 150 checks the access right of a user of the information processing terminal 200, attempting to perform an access, according to a request of the server application 121 as described above. In this embodiment, the access right control table 161 is generated beforehand to be stored in a storage apparatus, which is not shown, in the information processing support server 100. As shown in Figure 7, a log-on ID specifying a user, a password, and a validity term of an access right are registered in each line of the access right control table 161 with associating them with each other. Owing to this, the access right checker 150 refers to the access right control table 161 to judge the presence of the access right of the user on the basis of a

The information processing terminal 200 comprises a client application 220 and Web browser 230. In addition, the information processing terminal 200 can be realized with each of various household electric appliances such as a TV set embedding a computer, a game machine, portable information equipment such as a cellular phone and an electronic note, and other information terminal equipment with a communication function as well as a general computer system such as a personal computer, a workstation, a notebook computer, or the combination of them. Therefore, although this is not described in drawings, as hardware configuration, the information processing terminal 200 comprises a CPU, memory, a display unit such as a display for displaying Web-page, input devices such as a keyboard and a mouse for adding attached-information to the Web-page displayed on the display unit, and a connection interface for connecting the information processing terminal 200 to the communication network 400.

The client application 220 realizes collaboration on WWW contents that is performed between the server application 121 in the information processing support server 100 and another information processing terminal 200. Concretely, the client application 220 opens a collaboration Web window 221, where the Web-page for performing the collaboration is displayed, on a display screen of the display unit. In addition, the client application 220 displays the tool bar 222 for easily inputting commands for using various functions provided by the information processing support server 100, on the display screen. Here, the tool bar 222 provides commands in the shape of tool buttons by gathering the commands for using functions, provided by the information processing support server 100, such as performing annotation, and instructing the generation of a URL list. A user can use each of the functions by clicking a tool button, denoting a desired function, in the tool bar 222. In addition, the tool bar 222 is

The Web browser 230 opens Web window on a display screen of the display unit, and displays WWW contents in the shape of Web-page. Although this is used for reference to an ordinary Web-page without any collaboration, this can be used before starting the collaboration for making the information processing support server 100 check an access right, down-loading the client application 220, and inheriting predetermined settings. Therefore, if these functions can be realized by another means (for example, to provide hot keys), the Web browser 230 is not an indispensable component.

First, the operation at the time of adding the attached-information to the WWW contents will be described by using flow charts shown in Figures 2 and 3. This operation comprises, in rough classification, the operation of the

First, a user who is a customer (hereinafter, this is called a customer user) sends a log-on ID to the information processing support server 100 by using the Web browser 230 in the information processing terminal 200 and the TCP/IP network 210 (step 201). Concretely, for example, with providing WWW contents for performing log-on in the information processing support server 100, the customer user accesses the WWW contents for log-on from the information processing terminal 200 to input the log-on ID.

Next, the information processing support server 100 activates the client application 220 in the information processing terminal 200 (step 204). At this time, if there is not the client application 220 in the information processing terminal 200, the information processing support server 100 transmits the client application 220 to the information processing terminal 200 to install and activate the client application 220. Owing to this, the client application

220 opens the collaboration Web window 221 on a display screen of the display unit of the information processing terminal 200 to display the tool bar 222. In addition, the client application 220 obtains the UAI from the HTTP cookie to issue a connection request to the session managing section 131 in the information processing support server 100 by using the UAI as a parameter (step 205).

Next, the session managing section 131 in the information processing support server 100 assigns a unique session ID to the UAI of the connection request received, and informs the cache manager 122 of a pair of the UAI and session ID (step 206). The cache manager 122 retains the pair of the UAI and session ID received, and generates the URL attached-data control table 162 on the basis of this information (step 207). Here, the cache manager 122 generates a table, which associates UAIs with session IDs and is shown in Figure 10, and stores the table in the storage apparatus not shown. In addition, after informing the cache manager 122 of the pair of the UAI and session ID, the session managing section 131 transmits the session ID to the client application 220 in the information processing terminal 200 (step 208).

The client application 220 in the information processing terminal 200 newly issues a connection request to the session managing section 131 by using the session ID, received from the session managing section 131 in the information processing support server 100, as a parameter to establish a session with the information processing support server 100 (step 209).

Owing to the operation described above, a session is established between the information processing support server 100 and information processing terminal 200, and hence preparation is completed, the preparation which is for attached-information, added to WWW contents in the information processing terminal 200, being managed in the information processing support server 100.

Subsequently, the client application 220 obtains the WWW contents,

In addition, if annotation data is inputted as attached-information, the annotation data is sent to the information processing support server 100 sequentially. In the information processing support server 100, the session managing section 131 retains the annotation data, which is received, in memory (step 212).

If the data filled in the form is submitted, the cache manager 122 in the information processing support server 100 registers the form data in the URL attached-data control table 162. Then, the cache manager 122 informs the session managing section 131. In addition, if a command ending the annotation is inputted, the

session managing section 131 in the information processing support server 100 generates the annotation data file 170 not only to retain the annotation data, but also to register its file name in the URL attached-data control table 162. In addition, since the session managing section 131 always has the session ID as a parameter, it is possible to register the file name in a corresponding record of the URL attached-data control table 162 on the basis of the session ID.

If a transaction name is inputted, the client application 220 in the information processing terminal 200 displays a panel for inputting the transaction name, on a display screen, and hence the customer user inputs the transaction name on the panel (step 214). Then, the information processing terminal 200 sends the transaction name to the information processing support server 100 by the operation of clicking an OK button or the like. At the time of receiving the transaction name, the cache manager 122 in the information processing support server 100 registers the transaction name in the URL attached-data control table 162 (step 215).

In addition, if there is a field for inputting a transaction name in a form of WWW contents, the customer user can also input the transaction name at the step 211. In this case, the transaction name is registered in the URL attached-data control table 162 when the input of the attached-information is verified at the step 213.

Finally, the customer user logs off by clicking a log-off tool button in the tool bar 222 to disconnect the information processing terminal 200 from the information processing support server 100 (step 216). Owing to this, the session is closed, and the attached-information added to the WWW contents in the information processing terminal 200 is stored in the information processing support server 100.

Next, the operation of reproducing WWW contents where attached-information is added will be described by using flow

charts in Figures 4 to 6. In this embodiment, if the information processing support server 100 stores attached-information and the information processing terminal 200 issues an access request corresponding to the URL associated with the attached-information, the WWW contents having the URL and the attached-information associated with the URL are sent from the information processing support server 100 to the information processing terminal 200. Therefore, depending on a use style, if the information processing support server 100 stores the attached-information of the WWW contents when the information processing terminal 200 obtains a predetermined WWW contents via the information processing support server 100, it is also possible to automatically deliver the WWW contents to the information processing terminal 200 after adding the attached-information to the WWW contents. Nevertheless, here, in consideration of application to the Call Center, operation will be described, the operation of selecting a URL from a URL list so that an agent can selectively access WWW contents to which the agent should refer, that is, the WWW contents where the attached-information such as a question is added.

As methods for the information processing terminal 200 accessing the URL list, various methods can be provided, but, here, as a typical example, a method for logging on the information processing support server 100 similarly to an ordinary log-on, and a method for accessing WWW contents where the URL list is generated will be described.

The operation for accessing a URL list similarly to the ordinary log-on will be described by using Figures 4 and 5. This operation consists of, in rough classification, the operation of the information processing terminal 200 establishing a session with the information processing support server 100 (steps 301 to 309 shown in Figure 4), and the operation of the information processing terminal 200 performing the work of adding attached-information to the WWW contents that is an object of the work and reproducing the WWW contents (steps 310 to 320 shown in Figure 5).

First, an agent sends a log-on ID to the information processing support server 100 by using the Web browser 230 in the information processing terminal 200 and the TCP/IP network 210 (step 301). Concretely, similarly to the case of a customer user described above, the agent accesses the WWW contents for log-on from the information processing terminal 200 to input the log-on ID.

Next, at the time of receiving the log-on ID via the TCP/IP network 110, the server application 121 in the information processing support server 100 makes the access right checker 150 check an access right of the agent (step 302). The access right checker 150, as described above, refers to the access right control table 161 to check whether the agent having the log-on ID has the access right. Then, if the access right is not verified, the server application 121 executes error handling, and stops its processing. If the access right of the agent is verified, next, the server application 121 requests the UAI manager 140 to obtain a new UAI (step 303). Furthermore, the server application 121 sets the UAI, which is obtained, to an HTTP cookie.

Next, the information processing support server 100 activates the client application 220 in the information processing terminal 200 (step 304). At this time, if there is not the client application 220 in the information processing terminal 200, the information processing support server 100 transmits the client application 220 to the information processing terminal 200 to install and activate the client application 220. Owing to this, the client application 220 opens the collaboration Web window 221 on a display screen of the display unit of the information processing terminal 200 to display the tool bar 222. In addition, a tool button for generating a URL list is provided in the tool bar 222. Furthermore, the client application 220 obtains the UAI from the HTTP cookie to issue a connection request to the session managing section 131 in the information processing support server 100 by using the UAI as a parameter (step 305).

Next, the session managing section 131 in the information processing support server 100 assigns a unique session ID to the UAI of the connection request received, and informs the cache manager 122 of a pair of the UAI and session ID (step 306). The cache manager 122 retains the pair of the UAI and session ID received, and generates the URL attached-data control table 162 on the basis of this information (step 307). In addition, after informing the cache manager 122 of the pair of the UAI and session ID, the session managing section 131 transmits the session ID to the client application 220 in the information processing terminal 200 (step 308).

The client application 220 in the information processing terminal 200 newly issues a connection request to the session managing section 131 by using the session ID, received from the session managing section 131 in the information processing support server 100, as a parameter to establish a session with the information processing support server 100 (step 309).

Owing to the operation described above, the session is established between the information processing support server 100 and information processing terminal 200, and hence preparation is completed, the preparation which is for attached-information, to which the WWW contents are added in the information processing terminal 200, being obtained.

Subsequently, by clicking a URL list generation button in the tool bar 222 in the information processing terminal 200, a URL list generation request is transmitted from an applet, attached to this tool button, to the URL list generator 123 in the information processing support server 100 (step 310). At this time, a log-on ID is sent together as a parameter.

At the time of receiving the request, the URL list generator 123 in the information processing support server 100 refers to the condition list 163 (see Figure 9) to generate a URL list in an HTML format on the basis of conditions suitable to the log-on ID

Next, by the agent selecting the desired URL from the URL list displayed in the collaboration Web window 221 in the information processing terminal 200 and clicking the URL, WWW contents acquisition request is transmitted from the list selection applet to the URL list selector 124 in the information processing support server 100 (step 313). At this time, the session ID corresponding to the URL selected is transmitted together as a parameter.

At the time of receiving the request, the URL list selector 124 in the information processing support server 100 obtains WWW contents in the URL, which is specified, from the WWW server 300 (see Figure 1). In addition, the URL list selector 124 refers to the URL attached-data control table 162. If there is a form in the WWW contents and form data filled in its fields is registered, the URL list selector 124 restores the form data (step 314). Then, by embedding the form data, which is restored, in the fields corresponding to the form in the WWW contents obtained, the URL list selector 124 transmits the WWW contents to the client application 220 in the information processing terminal 200 (step 315).

In addition, if a file name of the annotation data file 170 is registered when the URL list selector 124 refers to the URL attached-data control table 162, it is necessary to make the information processing terminal 200 obtain the annotation data, for which there are two methods.

One is a method for supplying the annotation data from the information processing support server 100. In this case, first,

the URL list selector 124 calls the annotation reproducer 132 in the session manager 130 with a session ID as a parameter (step 316). The annotation reproducer 132 refers to the annotation data file 170 to simulate the occurrence of annotation. Then, the annotation reproducer 132 transmits the annotation data to the information processing terminal 200, which is operating, via a session specified by the session ID (step 317).

Another is a method for obtaining the annotation data from an apparatus except the information processing support server 100. This requires that the annotation data is stored in a storage apparatus, which is accessible, such as an external storage apparatus connected to the information processing terminal 200. In this case, the information processing support server 100 sends only the file name of the annotation data file 170 with the WWW contents to the information processing terminal 200. Then, the information processing terminal 200 reads the annotation data file 170, specified by the file name received, from the storage apparatus (step 318).

These two methods can also be compositely used according to an operating environment of the information processing terminal 200 instead of using any one of these methods.

Next, the client application 220 in the information processing terminal 200 displays the WWW contents, received from the information processing support server 100, in the collaboration Web window 221 (step 319). If annotation data is added to the WWW contents, the client application 220 reproduces the annotation, and synthesizes and displays the annotation with the WWW contents.

Finally, the agent logs off by clicking a log-off tool button in the tool bar 222 to disconnect the information processing terminal 200 from the information processing support server 100 (step 320). In addition, before closing the session, it is also possible to perform editing work of the form data and annotation data such as addition, deletion, and modification. In this case, the

Next, the operation of accessing WWW contents for generating a URL list will be described with reference to Figure 6. In this operation, since log-on is performed from a special URL list generation WWW contents, a session is established at the time of accessing the URL list generation WWW contents. Therefore, the operation for establishing the session is not performed in the operation after the log-on shown in Figure 6.

Next, at the time of receiving the log-on ID via the TCP/IP network 110, the server application 121 in the information processing support server 100 makes the access right checker 150 check an access right of the agent (step 402). The access right checker 150, as described above, refers to the access right control table 161 to check whether the agent having the log-on ID has the access right. Then, if the access right is not verified, the server application 121 executes error handling, and stops its processing. If the access right of the agent is verified, next, the server application 121 requests the UAI manager 140 to obtain a new UAI (step 403). Furthermore, the server application 121 sets the UAI, which is obtained, to an HTTP cookie.

- 32 -

In addition, after recognizing that it is the log-on from the URL list generation WWW contents, the URL list generator 123 in the information processing support server 100 refers to the condition list 163 to generate a URL list in an HTML format on the basis of conditions suitable to the log-on ID (step 405). Then, the URL list generator 123 sends the URL list generated, and the list selection applet, used for accessing a URL in the URL list, to the client application 220 in the information processing terminal 200 (step 406). Owing to this, the URL list is displayed in the collaboration Web window 221, and hence it becomes possible to select a desired URL by the agent clicking the URL.

Since the operation after this is the same as the operation after the step 313 that is described by using Figure 3, its description will be omitted.

As described above, according to this embodiment, attached-information added to WWW contents is stored in the information processing support server 100. Therefore, it is possible to separate the operation in the information processing terminal 200 into the work of adding the attached-information to the WWW contents and the work of reproducing the WWW contents to which the attached-information is added. Thus, if this embodiment is applied to collaboration by a plurality of information processing terminals 200, it is not necessary that all the information processing terminals 200, which participate in the collaboration, establish sessions at the same time. Therefore, if this embodiment is applied to the customer counseling service, customer users can access the information processing support server 100 at arbitrary time, and can add questions or the like. Furthermore, agents can access the information processing support server 100 and can verify the questions or the like that are added to the WWW contents at any time.

Next, such a concrete embodiment that this embodiment is applied to a system in a Call Center will be described by using Figures 11 to 13. Here, it is assumed that an object is WWW contents having a URL of "http://www.qa.co.jp/pc/sheet1.html" and a customer user inputted attached-information.

With referring to Figure 11 showing the WWW contents (Web-page) in such a state that the customer user inputted the attached-information, an arrow showing a specific position in an image of Web-page is written as annotation data. In addition, an input field of a "customer number" specifying a customer user and an input field of questions are provided as fields of a form, and text data is entered respectively.

- 34 -

Next, if an agent operates the information processing terminal 200 so as to access the information processing support server 100 from the information processing terminal 200 and generate a URL list, the collaboration Web window 221 is opened in the display unit of the information processing terminal 200, and the URL list as shown in Figure 13 is displayed. In the URL list in Figure 13, selection items 1301, 1302, and 1303, in each of which a session date and time and a customer number are displayed, are displayed. These selection items 1301, 1302, and 1303 are linked to the WWW contents having the corresponding URLs. Therefore, the user can access corresponding WWW contents by clicking an arbitrary selection item in the URL list.

In addition, it is assumed that the agent has an access right to all the sessions shown in Figure 12. Therefore, in the URL list shown in Figure 13, all of the three sessions registered in the URL attached-data control table 162 shown in Figure 12 are listed. In Figure 12, since a question (attached-information) in the session 1 and a question (attached-information) in the session 3 are about the same WWW contents, they are displayed in a lot with binding them with the URL. In this manner, a URL list is not always linked only to URLs, but it is possible to flexibly design the URL list so that users can easily watch or can easily operate the URL list. In addition, as shown in Figure 12, a URL list itself is given a URL different from the WWW contents shown in Figure 11.

- 35 -

Nevertheless, WWW contents can also be directly obtained by the information processing terminal 200 from the WWW server 300. In this case, the information processing support server 100 returns only a URL, corresponding to the access request, and attached-information associated with the URL to the information processing terminal 200. In the information processing terminal 200, WWW contents acquisition request having the URL is automatically generated. With corresponding to this request, the WWW contents having the URL is transmitted from the WWW server 300 to the information processing terminal 200. The information processing terminal 200 synthesizes the WWW contents, which are obtained in this manner, and the attached-information of the WWW contents, and displays the WWW contents, which are synthesized, in the collaboration Web window 221.

- 36 -

Furthermore, it is possible to use this embodiment for simple information exchange among members without any mail system. Concretely, it is also possible to use this embodiment in such a form that a plurality of members, who will travel together, access WWW contents for providing information relating to travels and write information respectively to exchange information.

As described above, according to the present invention, it becomes possible that a plurality of users share information added to WWW contents, and to refer to and modify WWW contents with attached-information at any time.

In addition, it is possible to automatically deliver WWW contents with attached-information to predetermined users.

Furthermore, it is possible that a user accesses WWW contents with attached-information by using a URL list.